


HYTOWER TECHNICAL DRAWINGS 2020



MASS & DIMENSIONS



1'-8" [0,52m]

5'-0" [1,52m]


> 50'-6" [15,40m] 53'-0" [16,16m]


40'-0" [12,19m]

0'-11" [0,28m]

2'-6" [0,76m]


> 4'-0" [1,22m]













$\label{eq:constraint} Drawings\ may\ show\ the\ HYTOWER\ equipped\ with\ optional\ accessories.\ May\ be\ sold\ separately.$






$\label{eq:constraint} Drawings \ may \ show \ the \ HYTOWER \ equipped \ with \ optional \ accessories. \ May \ be \ sold \ separately.$






$\label{eq:constraint} Drawings \ may \ show \ the \ HYTOWER \ equipped \ with \ optional \ accessories. \ May \ be \ sold \ separately.$





Drawings may show the HYTOWER equipped with optional accessories. May be sold separately.






 $\label{eq:constraint} Drawings\ may\ show\ the\ HYTOWER\ equipped\ with\ optional\ accessories.\ May\ be\ sold\ separately.$








CAPACITY: 150lbs/ft² (732kg/m²)

 $\label{eq:constraint} Drawings\ may\ show\ the\ HYTOWER\ equipped\ with\ optional\ accessories.\ May\ be\ sold\ separately.$






FLOOR STABILIZERS, EXTENSIONS AND LEVELLING JACKS

Drawings may show the HYTOWER equipped with optional accessories. May be sold separately.






Drawings may show the HYTOWER equipped with optional accessories. May be sold separately.







Drawings may show the HYTOWER equipped with optional accessories. May be sold separately.



A THOROUGH UNDERSTANDING OF THE INTER-RELATED LOADINGS SHOWN IN THIS RIGGING PLAN IS NEEDED IN ORDER TO SAFELY USE THE HYTOWER AND TAKE FULL ADVANTAGE OF THE MANY RIGGING OPPORTUNITIES IT OFFERS.

The HYTOWER offers a variety of rigging options with regard to load capacity, placement and type.


There are rigging pipes, trusses, roof rigging points and side overhang rigging beams.

This rigging plan locates and defines these rigging features, includes load capacity for each and describes maximum combinations of loads amongst features.

Take note of exclusions, maximum sub-totals in a group, load balance requirements, and maximum load bearing capacity.

The maximum load on the structure is less than the sum of the maximum load on each rigging feature.

Refer to Operator's Manual for procedures in regards to proper setup and setup methods of the tower and its options.




The information contained in the current document is final and must be considered as such. They are derived from design briefs and summarized to help the user plan rigging configurations safely. It is therefore mandatory that the user follows and respects the capabilities and limitations described herein. Overloading of stage components above their specified capacity may result in structural failure, equipment damage, injury or death. Stageline cannot be held responsible if the user, himself or subcontractors under his supervision, derogate from this document and/or the approved rigging plan. If a desired configuration cannot meet these requirements, the user must contact Stageline to analyse the case and obtain further instructions. Special restrictions and limitations may apply.

Certain authorities may require that a rig configuration plan, signed and sealed by a recognized member of a professional body, be available to allow the stage to be setup on their territory. This document was not intended to and cannot be used or considered as an official document or certificate to serve this purpose. Contact responsible authorities or Stageline for details.

Drawings may show the HYTOWER equipped with optional accessories. May be sold separately.

- DIVISION LOCATION


RENTAL DIVISION



Drawings may show the HYTOWER equipped with optional accessories. May be sold separately.







MAXIMUM LOAD BEARING CAPACITY: 15290 LB (6935 KG)

CAPACITY OF POINTS:

- P1: 4400 lb (1995 kg)
- P2: 4400 lb (1995 kg) per pair
- P3: 4400 lb (1995 kg) per pair
- P4: 3600 lb (1632 kg) per pair
- Truss area A: 10000 lb (4536 kg)

FOLLOWSPOT PLATFORM CAPACITY:

- 5290 lb (2400 kg) total
- 1322 lb (600 kg) per platform
- Follow spot platform capacity includes all equipment and workers.

RIGGING RESTRICTIONS:

- Total load on P1, P2 and P3 must not exceed 4400 lb (1995 kg). Total load on P1', P2' and P4' must not exceed 3600 (1632 kg).
- Paired points are located on each side of the Lengthwise Axis.
- P2 must be used in pair (symmetric load only).
- P3 must be used in pair (symmetric load only).
- P4 must be used in pair (symmetric load only).
- P1 to P4 points can be installed at 3', 5' 7' or 9' from tower center.
- Loads on the follow spot platforms must be within 5'5" (1.65m) from the edge of the tower.
- If a video screen is used, refer to VIDEO SCREEN RIGGING RESTRICTIONS on page 4 for details and limitations.
- If the platforms are not installed, the structure can be used for rigging. Maximum load bearing capacity remains the same. If they are installed, no rigging is allowed on the platforms side.

Drawings may show the HYTOWER equipped with optional accessories. May be sold separately.



VIDEO SCREEN RIGGING RESTRICTIONS:

- Total load on P1s, P2s and P3s must not exceed 4400 lb (1995 kg) when Truss Area A is not used.
- When using Truss Area A, refer to chart below for residual point capacity.
- Screen can only be installed in short configuration (refer to page 2 of RIGGING PLAN for details).
- Maximum screen dimensions without additional ballast added to the structure : 16' x 9' (W x H). Maximum screen height from deck to bottom of screen : 28' in landscape view, 21' in portrait view.
- Maximum screen dimensions with additional ballast added to the structure : 24' x 16' (W x H). Maximum screen height from deck to bottom of screen : 15' in landscape view, 7' in portrait view.
- No follow spot platform can be used when screen is installed.

NOTE :

• No rigging truss is provided for truss area A.

RESIDUAL LOADS CHART			
Truss Area A		Total load on points	
Lbs	Kg	Lbs	Kg
10000	4536	0	0
9000	4082	400	181
8000	3628	800	363
7000	3175	1200	544
6000	2721	1700	771
5000	2268	2100	952
4000	1814	2600	1179
3000	1361	3000	1361
2000	907	3500	1587
1000	454	3900	1769
0	0	4400	1995

